

# TSI STONE GLOSS



Coverage Chart for TSI Stone Gloss		
SUBSTRATE	Sq./Ft per Gallon	PACKAGING
Marble/Granite	250-350	Qts., Gals, 5 – Gallons, Drums

## DATA SHEET of Specifications

- **Product Description: TSI Stone Gloss**

**TSI Stone Gloss** is a unique acrylic product designed to enhance the natural look and color of all flamed, sandblasted, split face, tumbled and textured surfaces including limestone, granite, slate, marble, cast and natural stone. **TSI Stone Gloss** allows vapor transmission while offering a slip resistant, scuff resistant and water resistant surface. **TSI Stone Gloss** is UV transparent and non-yellowing. Due to the difference of each material several inconspicuous test patches should be completed to assure maximum performance. User must determine suitability of the product for their intended use.
- **Basic Uses**

**TSI Stone Gloss** can be used to enhance Granite, marble, slate, limestone, monuments, concrete, masonry, brick and stone. **TSI Stone Gloss** is mainly used for vertical and horizontal natural stone surfaces.
- **Sample Testing**

A test application is strongly suggested due to the differences of each material. User must determine suitability of the product for their intended use.

**FOR NON-POLISHED SURFACES**

# TSI STONE GLOSS

- **Application**

- **New Installation-Before Grouting**

Apply **TSI Stone Gloss** on all surfaces prior to grouting. This step will allow quick and easy clean up after grouting. Grout can stain many materials if this procedure is not used prior to grouting. Apply **TSI Stone Gloss** using a clean cotton towel, lambs wool applicator, rayon mop or pneumatic sprayer. Apply enough to wet the surface. (See coverage charts.) Be careful not to saturate the open grout joints. Allow **TSI Stone Gloss** to cure for 24 hours before continuing with grouting procedure.

- **New Installation-After Grouting**

All excess grout residue glaze must be removed from surface, then apply **TSI Stone Gloss** to the grout joints using a paint brush or sponge. On larger areas or more porous materials, a second application may be applied over the entire surface including the grout joint in the same manner as mentioned above. These procedures will protect the grout joint as well as the tile or stone surface.

- **Existing Installation**

Remove any existing wax and topical matter with appropriate stripping agent. If surface shows imbedded dirt or stains remove before applying **TSI Stone Gloss**. After allowing substrate to thoroughly dry apply **TSI Stone Gloss** as directed above.

- **Cure Time**

Although **TSI Stone Gloss** requires a 24 hour cure time, it will be dry to the touch in 30-45 minutes and may be used for normal foot traffic. For best results the area should be kept dry and free from staining materials for 72 hours.

- **Limitations**

Any previously treated, stained or painted surface must have a test application to ensure compatibility. A test application is also recommended if exact coverage figures are required. Do not apply to a frosted or saturated surface. Do not spray in strong wind conditions. Remove any overspray from glass, metal or vinyl surfaces immediately after application by wiping with a damp cloth, followed by wiping with glass cleaner. Clean tools immediately after application with water.

- **Precautions**

Keep container tightly closed when not in use. Do not ingest. Avoid contact with skin and eyes. In case of contact with skin or eyes, flush with clear water for 15 minutes.

- **Storage**

Stored at 77 ° F **TSI Stone Gloss** will have a shelf life of 12 months.

**FOR NON-POLISHED SURFACES**